

PART NUMBER	STAGES	TONNE PER STAGE	L1	CLOSED CRS	STROKE	OPEN CRS	S1	BORE S2	BORE S3	BORE	A&	B&	C&	D	E	BSP	OIL CAPACITY (LITRES)
METRIC STAGE TIPPING CYLINDERS																	
M900/A*	3	13 - 9 - 5	1245		2821	4066	110	90	70	120	50	31.75	109	1/2"			18.6
M900/B*	3	13 - 9 - 5	914		2032	2946	110	90	70	120	50	31.75	41	1/2"			13.4
M900/C*	3	13 - 9 - 5	1092		2449	3541	110	90	70	120	50	31.75	80	1/2"			16.2
M900/E*	3	13 - 9 - 5	1016		2323	3339	110	90	70	120	50	31.75	46	1/2"			15.3
M901/A CHROMED	3	11 - 7 - 4	924		1993	2917	100	80	60	110	45	25.4	74	1/2"			10.5
M902/C*	2	13 - 9	914		1370	2284	110	90	●	120	50	31.75	50	1/2"			10.8
M909/E CHROMED	2	11 - 5	914		1384	2298	100	80	●	110	45	25.4	63	1/2"			8.1
IMPERIAL STAGE TIPPING CYLINDERS																	
C901/A	3	10 - 7 - 4	924		1993	2917	3.75"	3"	2.375"	105	44.45	25.4	72	1/2"			9.7
C909/A	2	10 - 5	876		1375	2251	3.75"	2.75"	●	105	44.45	25.4	45	1/2"			7.5
C909/E	2	10 - 5	914		1384	2298	3.75"	2.75"	●	105	44.45	25.4	78.5	1/2"			7.6
C916/A	2	4 - 2	533.5		700	1233.5	2.375"	1.75"	●	70	31.75	20.25	38	3/8"			1.5
C916/B	2	4 - 2	660		953	1613	2.375"	1.75"	●	70	31.75	20.25	38	3/8"			2.1
C916/C	2	4 - 2	737		1107	1844	2.375"	1.75"	●	70	31.75	20.25	38	3/8"			2.4

* = AVAILABLE IN CHROMED STAGES

